



better products
cleaner environment

ACTION 150 S **High Performance Stripper**

Product Description

Formulated with the ideal blend of high-grade solvents, ammonia and patented detergent technology, ***ACTION 150 S*** effectively strips heavy build up of floor waxes and metal finishes. It is a powerful yet cost effective product that will do the job where other standard strippers fail.

Areas of Use

ACTION 150 S should be used with confidence to strip polishes from vinyl, rubber, parquet, cement, slate, marble, granite, terrazzo and most types of tiles.

Special Features

- Strips through tough commercial waxes, sealers and finishes that conventional strippers cannot handle.
- Does the job much faster, saving both time and labour. This makes for extremely efficient stripping of floors.

Directions for Use

Dilution rate varies according to the degree of wax build.

Heavy build up, dilute 1:5 with water.

Normal build up, dilute 1:12 with water.

- Test on isolated floor area to ensure no adverse effect occurs.
- Spread solution on floor, allow to set for about 5 mins. Scrub using a rotary machine with black pad for total stripping, or green pad for surface stripping. Do not use machine agitation for wood floors, just mop. Vacuum up the residue with a wet/dry cleaner.
- Mop and rinse thoroughly with water to remove all residues. Allow complete drying before applying a good sealer or finish such as ***PREMIUM SHIELD*** or ***SUPER COATING***.

Precautions

As with most chemical products, avoid ingestion and eye contact. If ingested, dilute by drinking water and seek medical help. If product enters eyes, flush with water and seek medical help. Rubber gloves should be worn when handling product. Wash hands thoroughly with soap and water after use.

SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION				
Product Identifier: ACTION 150 S		Supplier: Klenco (Singapore) Pte Ltd. Address: 18 Gul Crescent, Singapore 629527 Department: Chemical Person in Charge: Chemist		
Other means of identification: High Performance Stripper		Phone: (65) 6862 3388		
Date of SDS: 01 January 2024		Fax: (65) 6861 7575		
Recommended use and restriction on use: ACTION 150 S should be used with confidence to strip polishes from vinyl, rubber, parquet, cement, slate, marble, granite, terrazzo and most type of tiles.		Email: info@klenco-asia.com Emergency contact: (65) 6862 3388 Ext 249		
SECTION 2 - HAZARDS IDENTIFICATION				
GHS classification: Acute toxicity: Category 3 Skin irritation: Category 2				
GHS label elements: Pictogram:		Signal Words: Danger		
				
Hazard statements: H301: Toxic if swallowed. H315: Causes skin irritation. H335: May cause respiratory irritation.				
Precaution statements: P102: Keep out of reach of children. P262: Do not get on skin. P280: Wear protective gloves and clothing.				
SECTION 3 - COMPOSITION/ INFORMATION ON INGREDIENTS				
Chemical Identification	Component & Composition	Chemical Formula	CAS NO.	EC NO.
Ethylene Glycol Butyl Ether	< 20.0%	CH3(CH2)3OCH2CH2OH	111-76-2	203-905-0
Ethanolamine	< 10.0 %	C2H7O	141-43-5	205-483-3
Sodium Hydroxide	< 5.0 %	NaOH	1310-73-2	215-185-5
Alkyl Dimehtylamine Oxide	< 2.0 %	C15H33NO	70592-80-2	274-687-2
Nonyl Phenol Ethoxylate	< 2.0 %	C33H60O10	26571-11-9	247-816-5
Sodium EDTA	< 0.5 %	C10H12N2Na4O8	64-02-8	200-573-9
Aqueous Ammonia	< 1.0 %	NH4OH	1336-21-6	215-647-6
Water	> 80.0 %	H2O	7732-18-5	231-791-2
SECTION 4 – FIRST AID MEASURES				
Inhalation: Move to area of fresh air. If breathing has stopped, artificial respiration should be started. Oxygen may be administered if available. Call a physician. Never give anything by mouth to an unconscious person.				
Skin contact: Wash with large amounts of soap and water. If irritation persists, consult a physician.				
Eye contact: Flush with cool water for at least 15 minutes. Then consult a physician immediately.				
Ingestion: Induce vomiting. Dilute by drinking water. Call a physician immediately.				
Notes to Physicians: Treatment should be directed at preventing absorption, administering to symptoms (if they occur), and providing supportive therapy.				
SECTION 5 – FIRE-FIGHTING MEASURES				
Suitable fire-extinguishing media: Water, dry chemical, carbon dioxide and foam.				
Specific hazards arising from the chemical: Burning can produce carbon dioxide, carbon monoxide and traces of nitrogen oxides.				
Special protective actions for fire fighters: Fire fighters may be exposed to the products of combustion should wear a self-contained breathing apparatus with full protective equipment.				
SECTION 6 - ACCIDENTIAL RELEASE MEASURE				
Personal precautions, protective equipment, and emergency measures: Use proper protective equipment (chemical protection suit, gloves, goggles, mask, etc).				
Environmental precautions: Chemical substance should not be released into the environment (water, soil).				
Methods and materials for containment and cleaning up: Safely stop discharge. Contain material, as necessary, with dike or barrier. Stop material from contaminating soil or from entering sewers or bodies of water. Cover spills with absorbent clay, sawdust or inert material and place in closed chemical waste containers. Dispose of according to applicable local, state and federal regulations.				
SECTION 7 - HANDLING AND STORAGE				
Precaution for safe handling: Wash thoroughly after handling, especially before eating and drinking. Wash contaminated goggles, face-shield, and gloves. Launder contaminated clothing before re-use.				
Conditions for safe storage, including any incompatibilities: This product is a combustible liquid. Store in a cool, dry, well-ventilated area at room temperature. Keep away from any possible source of ignition. Store away from any oxidizing materials.				
Do not re-use empty container for food, clothing or products for human or animal consumption or where skin contact can occur.				

SECTION 8 - EXPOSURE CONTROLS/ PERSONAL PROTECTION	
Control parameters/ Occupational exposure limits:	ACGIH - TLV: Provide suitable personal protective equipment and/or ventilation to maintain exposure below TLV levels.
Appropriate engineering control measures:	Local exhaust ventilation is usually required, when vapours, mist, or dusts can be released.
Personal Protection:	Use the protective equipment such as protective Rubber/PVC gloves; safety glasses/ goggles.
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES	
Appearance & Odour:	Clear liquid with characteristic odour.
Solubility in water:	Complete.
Boiling Point:	100 ° C
Specific Gravity:	1.030 +/- 0.01 g/cm ³
PH:	13.0 +/-1.0
Flash Point (T.C.C.):	> 93° C Flammable Limits - Upper: Not applicable Lower: Not applicable
Vapour Pressure:	Not determined
Vapour Density:	Not determined
SECTION 10 - STABILITY AND REACTIVITY	
Reactivity/ In compatible materials:	Acids and oxidizing materials.
Chemical stability:	Stable under normal temperature and pressure.
Possibility of hazardous reaction:	Will not occur.
Condition to avoid:	Not applicable
SECTION 11 – TOXICOLOGICAL INFORMATION	
Acute toxicity: Oral:	Ingestion of high amount of product is fatal.
Skin or eye irritation:	This product contains sodium hydroxide solution that may cause irritation to eyes and/or skin.
SECTION 12 – ECOLOGICAL INFORMATION	
Toxicity:	Concentrations with a pH value of 10.5 or greater especially in fresh water may be fatal to fish and other aquatic organism. Can cause damage to aquatic plants and vegetation.
Persistence and degradability:	Product degrades readily by reaction of carbon dioxide in the air as well as decomposition by microorganism.
Bioaccumulative potential:	It is soluble in water and does not bio-accumulate.
SECTION 13 – DISPOSAL CONSIDERATIONS	
Disposal method:	Dispose of in an approved waste facility according to local regulations. It is recommended that an alternative be selected according to the following order of preference, based upon environmental acceptability: (1) Re-cycle or rework, if feasible (2) Incinerate at an authorized facility (3) Treat at an acceptable waste treatment facility.
SECTION 14 – TRANSPORT INFORMATION	
This material is non-regulated and no special requirement is necessary. HS Code: 34024100	
SECTION 15 – REGULATORY INFORMATION	
International regulation:	
Classification:	This product contains sodium hydroxide as an ingredient that is classified as corrosive under EC Classification.
Risk phrases:	R25 Toxic if swallowed. R37/38 Irritating to respiratory system and skin.
Safety phrases:	S02 Keep out of reach of children. S24 Avoid contact with skin. S36/ 37 Wear suitable protective clothing and gloves.
SECTION 16 – OTHER INFORMATION	
Hazard Rating: HMIS (Hazardous Materials Information System)	
HEALTH:	2
FLAMMABILITY:	0
REACTIVITY:	0
0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Extreme	

NOTICE: SDS is correct at date of publication. It is not necessarily fully adequate for every circumstance, nor to be confused with or followed in violation of applicable laws or insurance requirements. Health hazards and effects of over-exposure apply only to negligent handling or misuse of product in its concentrated form (as supplied); and not routine exposure to diluted product under normal use. No warranty, express or implied, of merchantability, fitness or accuracy of data is made; as such the vendor assumes no responsibility for injury or damages resulting from use of this product.